

Boat Manufactured By:



WELLCRAFT® 241 FISHERMAN

Length	24' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	300 hp
Fuel Capacity	87 gal
Weight as Tested	5,541 lbs

F300XCA

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2 on 12" Hydraulic Jack Plate
------------------------	--------------------------------

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	58° F / 57° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes optional deluxe T-Top, 12" hydraulic jack plate, 45 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_Wellcraft_241 Fisherman_F300XCA_3.27.19_BAY

Engine: Yamaha F300XCA

Boat: Wellcraft® 241 Fisherman

Configuration: Single

Test Date: 27-Mar-2019



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.9	1.3	3.88
1500	7.1	2.2	3.20
2000	8.7	3.6	2.40
2500	12.5	5.5	2.27
3000	22.3	6.9	3.23
3500	28.8	8.7	3.30
4000	34.3	11.8	2.90
4500	38.5	15.7	2.46
5000	43.7	19.8	2.21
5500	48.0	25.4	1.89
5950	52.4	26.7	1.96
0-20 MPH: 5.07 seconds 			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.