

Boat Manufactured By:

SEA PRO

25214 Hwy 121 • Whitmire, SC 29178
(803) 694-2644
seapromfg.com

SEA PRO 322 OFFSHORE

Length	32' 0"
Beam	10' 4"
Dry Weight (Boat Mfr. Pub)	8,500 lbs
Maximum HP	850 hp
Fuel Capacity	207 gal
Weight as Tested	10,718 lbs

F350XSA2 / LF350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 - 629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 20
Yamaha Part #	6CF-45932-20-00 / 6CE-45932-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	76° F / 72° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 4 batteries, safety and test equipment.

YPB#: PB_SEP_322 Offshore_TW_F350XSA2_2-17-2024_OCC



Engine: Yamaha F350XSA2 / LF350XSA2

Boat: Sea Pro 322 Offshore

Configuration: Twin

Test Date: 17-Feb-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.1	2.5	2.41
1500	8.3	4.4	1.91
2000	10.3	7.7	1.34
2500	14.2	12.1	1.17
3000	20.0	14.8	1.35
3500	29.2	17.0	1.71
4000	35.5	22.3	1.59
4500	41.2	28.8	1.43
5000	47.2	37.4	1.26
5500	53.1	50.1	1.06
6100	59.0	62.1	0.95
0-30 MPH: 8.84 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.