

Boat Manufactured By:



P.O. Box 26 • Amory, MS 38821

(662) 256-5636

www.nauticstarboats.com



NAUTIC STAR® 193 SC

Length	18' 9"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,100 lbs
Maximum HP	150 hp
Fuel Capacity	32 gal
Weight as Tested	3,035 lbs

F90XA

Horsepower	90 hp
Induction	EFI
Displacement	97 cu. in.
Weight (Estimated)	372 lbs
Gear Ratio	2.27

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	Even with Boat Bottom

PROPELLER(S)

Series	Talon™
Diameter x Pitch	13 1/2 x 14
Yamaha Part #	6EK-45947-00-00
Propeller Material	Painted Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	72° F / 65° F
Elevation (in feet above sea level)	234'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 1 battery, safety and test gear.

YPB#: PB_NST_193SC_F90XA_2016-03-10_DCK

Engine: Yamaha F90XA

Boat: Nautic Star® 193 SC

Configuration: Single

Test Date: 10-Mar-2016

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4	0.4	10
1500	5.3	0.7	7.57
2000	6.5	1.1	5.91
2500	7.7	1.9	4.05
3000	9.4	2.9	3.24
3500	16.6	3.4	4.88
4000	22.4	4.3	5.21
4500	26	5	5.2
5000	29.7	6.3	4.71
5500	32.9	7.7	4.27
5950	35.9	9.4	3.82

**Time to Plane : 4.19
 0-20 MPH: 5.84**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.