

Boat Manufactured By:

SEA PRO

25214 Hwy 121 • Whitmire, SC 29178
(803) 694-2644
seapromfg.com

SEA PRO 228 BAY

Length	22' 8"
Beam	8' 4"
Dry Weight (Boat Mfr. Pub)	2,325 lbs
Maximum HP	250 hp
Fuel Capacity	61 gal
Weight as Tested	3,781 lbs

F250XCB

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	556 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 84° F
Elevation (in feet above sea level)	250'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 2 batteries, optional hard top t-top, safety and test equipment.

YPB#: PB_SPR_228 Bay_F250XCB_8-23-2022_BAY



Engine: Yamaha F250XCB

Boat: Sea Pro 228 Bay

Configuration: Single

Test Date: 22-Aug-2022



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.3	1.4	3.79
1500	7.2	2.3	3.13
2000	8.5	4.0	2.13
2500	12.1	5.4	2.24
3000	26.0	6.5	4.00
3500	32.0	8.8	3.64
4000	36.6	12.1	3.02
4500	41.5	14.8	2.80
5000	45.9	18.5	2.48
5500	51.5	24.7	2.09
5900	55.7	26.1	2.13

Time to Plane: 2.85 seconds / **0-30 MPH: 5.94 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.