

Boat Manufactured By:



BENNINGTON
2805 Decio Drive • Elkhart, IN 46514
(574) 264-6336
www.benningtonmarine.com

BENNINGTON® 2550 GS

Length	27' 5.5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,572 lbs
Maximum HP	150 hp
Fuel Capacity	23 gal
Pontoons Diameter	2 / 25"
Weight as Tested	3,595 lbs

F115LB

Horsepower	115 hp
Induction	EFI
Displacement	111.8 cu. in.
Weight (Estimated)	377 lbs
Gear Ratio	2.15

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Talon® Series-SDS™
Diameter x Pitch	13 1/2 x 12
Yamaha Part #	6EK-45945-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	73° F / 53° F
Elevation (in feet above sea level)	785'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 18 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_BNT_2550GSR_F115LB_2014-05-21_PNT



Engine: Yamaha F115LB

F115LB

Boat: Bennington® 2550 GS

Configuration: Single

Test Date: 21-May-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.3	0.4	8.25
1500	5	0.7	7.14
2000	6.6	1.2	5.5
2500	8.6	1.7	5.06
3000	11.4	2.2	5.18
3500	14.7	2.9	5.07
4000	17.4	4	4.35
4500	19.5	4.9	3.98
5000	21.6	6.5	3.23
5500	23.8	8.4	2.83
5900	25.4	10.2	2.49

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.