

Boat Manufactured By:

ALUMA Craft

315 West St. Julien Street • St. Peter, MN 56082

(507) 931-1050

www.alumacraft.com

ALUMACRAFT COMPETITOR 205 TILLER

Length	20' 6"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	1,616 lbs
Maximum HP	200 hp
Fuel Capacity	45 gal
Weight as Tested	2,943 lbs

F115XB

Horsepower	115 hp
Induction	EFI
Displacement	1.8L
Weight (Estimated)	386 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/4" above boat bottom

PROPELLER(S)

Series	Aluminum Series
Diameter x Pitch	13-1/4 x 17
Yamaha Part #	6E5-45945-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	75° F / 64° F
Elevation (in feet above sea level)	1060'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 42 gallons of fuel, 4 batteries, bow-mounted trolling motor, safety and test equipment.

YPB#: PB_ALM_Competitor205Tiller_F115XB_2015-07-21_ALM



Engine: Yamaha F115XB

Boat: Alumacraft Competitor 205 Tiller

Configuration: Single

Test Date: 20-Jul-2015



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.1	0.4	10.25
1500	5.6	0.8	7.00
2000	7.0	1.2	5.83
2500	8.3	1.9	4.37
3000	11.6	2.5	4.64
3500	17.8	3.1	5.74
4000	23.1	4.0	5.78
4500	27.2	5.3	5.13
5000	30.9	6.7	4.61
5500	34.2	8.3	4.12
6100	38.6	10.2	3.78
0-20 MPH: 4.90 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.