

Boat Manufactured By:
REGULATOR

PO Box 49 • Edenton, NC 27932
 (252) 482-3837
 www.regulatormarine.com



REGULATOR 24 XO

Length	24' 4"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	4,700 lbs
Maximum HP	350 hp
Fuel Capacity	86 gal
Weight as Tested	6,315 lbs

F350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
Ventilation Plate Height	3" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 20
Yamaha Part #	6CE-45932-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	91° F / 84° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 33 gallons of fuel, 2 batteries, Jackplate, Dual Power Poles, Freshwater Tank, safety and test equipment.

YPB#: PB_REG_24_XO_F350XSA2_06-26-24_OCC

Engine: Yamaha F350XSA2

Boat: Regulator 24 XO

Configuration: Single

Test Date: 26-Jun-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	1.3	4.00
1500	7.0	2.3	3.11
2000	8.4	4.1	2.04
2500	9.4	6.7	1.41
3000	12.5	9.0	1.38
3500	29.0	10.0	2.90
4000	34.9	13.1	2.67
4500	40.4	16.1	2.52
5000	45.3	21.3	2.12
5500	51.9	28.5	1.82
6000	56.1	30.1	1.86
0-20 MPH: 7.80 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.