

Boat Manufactured By:



P.O. Box 1380 • Lexington, SC
(803) 755-6539
www.seahuntboats.com

SEA HUNT® GAMEFISH 25

Length	25' 6"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	4,700 lbs
Maximum HP	400 hp
Fuel Capacity	146 gal
Weight as Tested	6,683 lbs

F150XCA / LF150XCA

Horsepower	150 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	487 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/4 x 18
Yamaha Part #	68F-45978-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 81° F
Elevation (in feet above sea level)	300'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 2 batteries, safety and test gear.

YPB#: PB_SHT_Gamefish25_t_F150XCA_2017-08-16_OCC



Engine: Yamaha F150XCA /
LF150XCA

Boat: Sea Hunt® Gamefish 25

Configuration: Twin

Test Date: 16-Aug-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5	1.7	2.94
1500	7.3	2.9	2.52
2000	8.7	4.9	1.78
2500	11	6.1	1.8
3000	18.5	7.8	2.37
3500	25	9.3	2.69
4000	31.3	12.6	2.48
4500	36.1	16.3	2.22
5000	40.8	21.5	1.9
5500	45.3	28.5	1.59
5900	48.1	30.3	1.59
Time to Plane : 3.5 			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.