

Boat Manufactured By:



650 River Ave • South Gardiner , ME 4359
(207) 620-7998

www.southportboats.com

SOUTHPORT 33 FE

Length	32' 6"
Beam	10' 8"
Dry Weight (Boat Mfr. Pub)	9,200 lbs
Maximum HP	900 hp
Fuel Capacity	305 gal
Weight as Tested	11,836 lbs

XF425XSA2 / LXF425XSA2

Horsepower	425 hp
Induction	DI/VCT/DOHC
Displacement	5.6L
Weight (Estimated)	952 lbs
Gear Ratio	1.79:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	XTO Offshore
Diameter x Pitch	16-3/8 x 21
Yamaha Part #	6GR-45976-00-00 / 6GS-45976-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	46° F / 55° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 152 gallons of fuel, 3 batteries, safety and test gear.

YPB#: PB_SOU_33FE_T XF425XSA_10-23-18_OCC



Engine: Yamaha XF425XSA2 /
LXF425XSA2

Boat: Southport 33 FE

Configuration: Twin

Test Date: 23-Oct-2018



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.7	4.0	1.66
1500	9.5	5.6	1.70
2000	11.5	8.9	1.29
2500	18.2	12.3	1.48
3000	26.0	16.1	1.61
3500	32.6	22.9	1.42
4000	38.2	28.7	1.33
4500	44.0	38.1	1.15
5000	49.7	48.2	1.03
5500	55.3	62.5	0.88
6100	59.6	78.9	0.76
0-20 MPH: 4.28 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.