

Boat Manufactured By:
SEA FOX
BOAT WORKS
 2550 Highway 52 • Moncks Corner, SC
 (843) 761-6090
 www.seafoxboats.com



SEA FOX® 22XTR VIPER

Length	22' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,300 lbs
Maximum HP	250 hp
Fuel Capacity	62 gal
Weight as Tested	4,471 lbs

VF250XA

Horsepower	250 hp
Displacement	4.2 L
Weight (Estimated)	555 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4 on 6" Hydraulic Jack Plate
Ventilation Plate Height	2" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series 11™
Diameter x Pitch	15 1/4 x 18
Yamaha Part #	6CE-45934-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 85° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 1 battery, 6" hydraulic jack plate, safety and test gear.

YPB#: PB_SF_X_22XTRViper_VF250XA_2015-08-15_BAY

Engine: Yamaha VF250XA

Boat: Sea Fox® 22XTR Viper

Configuration: Single

Test Date: 15-Aug-2015



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	1.3	4
1500	7.2	2.4	3
2000	9.1	3.8	2.4
2500	16.7	5.3	3.15
3000	26.2	6.6	3.97
3500	31.3	8.4	3.73
4000	36.8	11.3	3.26
4500	42	15.1	2.78
5000	46.5	17.6	2.64
5500	50.8	22.2	2.29
6000	56	24	2.33
0-30 MPH: 4.16			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.