

Boat Manufactured By:

Hurricane

4310 Middlebury St. • Elkhart, IN 46516

(574) 522-8381

www.hurricaneboats.com



HURRICANE SD 2050

Length	20' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,990 lbs
Maximum HP	200 hp
Fuel Capacity	44 gal
Weight as Tested	4,265 lbs

F150XC

Horsepower	150 hp
Induction	EFI/VCT/DOHC
Displacement	2.7L
Weight (Estimated)	525 lbs
Gear Ratio	2:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance
Diameter x Pitch	14-1/4 x 17
Yamaha Part #	68F-45972-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	66° F / 72° F
Elevation (in feet above sea level)	860'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_HUR_SD 2050_F150XC_8-12-24_DCK

Engine: Yamaha F150XC

Boat: Hurricane SD 2050

Configuration: Single

Test Date: 12-Aug-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.4	0.8	5.50
1500	6.2	1.3	4.73
2000	7.2	1.9	3.76
2500	8.3	3.1	2.68
3000	10.4	4.6	2.26
3500	21.5	5.2	4.17
4000	26.7	6.4	4.20
4500	30.8	7.9	3.90
5000	36.1	9.4	3.86
5500	39.9	12.8	3.11
6100	45.3	15.5	2.92
0-20 MPH: 5.14 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.