

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946

(772) 465-0631

www.pathfinderboats.com

PATHFINDER 2600 HPS

Length	26' 2"
Beam	8' 10"
Dry Weight (Boat Mfr. Pub)	4,100 lbs
Maximum HP	450 hp
Fuel Capacity	104 gal
Weight as Tested	5,099 lbs

F350XSA2

Horsepower	350 hp
Induction	EFI/VC/T/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	2
------------------------	---

PROPELLER(S)

Series	Saltwater Series II HP
Diameter x Pitch	15 x 21
Yamaha Part #	6KA-45976-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	73° F / 71° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 1 battery, Hardtop, Hydraulic Jack Plate, safety and test equipment.

YPB#: PB_PAT_2600 HPS_F350XSA2_4-23-24_BAY



PICTURE SHOWN WITH OPTIONAL

Engine: Yamaha F350XSA2

Boat: Pathfinder 2600 HPS

Configuration: Single

Test Date: 23-Apr-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	1.2	4.34
1500	7.5	2.2	3.38
2000	9.3	3.9	2.35
2500	17.0	6.0	2.82
3000	26.9	7.4	3.62
3500	32.8	9.3	3.53
4000	39.4	12.4	3.19
4500	44.8	15.3	2.92
5000	51.0	20.3	2.52
5500	56.1	28.3	1.98
6100	60.9	31.6	1.93
0-20 MPH: 5.77 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.