

Boat Manufactured By:

 199 Extrusion Place • Hot Springs, AR
 (501) 262-5300
www.xpressboats.com

XPRESS X21 BAY

Length	21' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	1,898 lbs
Maximum HP	200 hp
Fuel Capacity	75 gal
Weight as Tested	3,208 lbs

F200XB

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Jack Plate	10" Hydraulic Jack Plate

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	13-3/4 x 19
Yamaha Part #	68F-45974-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	84° F / 74° F
Elevation (in feet above sea level)	320'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 3 batteries, bow-mounted trolling motor, battery charger, 10" hydraulic jack plate, safety and test gear.

YPB#: PB_XPR_X21Bay_F200XB_2016-11-01_ALM



Engine: Yamaha F200XB

Boat: Xpress X21 Bay

Configuration: Single

Test Date: 31-Oct-2016



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	0.8	5.88
1500	6.4	1.4	4.57
2000	8.0	2.5	3.20
2500	12.9	3.5	3.69
3000	23.6	4.1	5.76
3500	29.2	5.5	5.31
4000	34.2	7.9	4.33
4500	39.9	9.7	4.11
5000	44.5	13.8	3.23
5500	49.6	16.8	2.95
6000	52.0	19.5	2.67
0-30 MPH: 7.31 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.