

Boat Manufactured By:
 **CROWNLINE**
 11884 Country Club Road • West Frankfort, IL 62896
 (618) 937-6426
www.crownline.com

CROWNLINE® E4 XS

Length	24' 3"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,941 lbs
Maximum HP	300 hp
Fuel Capacity	55 gal
Weight as Tested	5,172 lbs

VF250XA V MAX SHO®

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	555 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Ventilation Plate Height	1 1/2" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 1/2 x 16
Yamaha Part #	6CE-45938-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	69° F / 69° F
Elevation (in feet above sea level)	405'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 25 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_CRO_E4XS_VF250XA_2016-05-24_DCK



Engine: Yamaha VF250XA V MAX

SHO®

Boat: Crownline® E4 XS

Configuration: Single

Test Date: 24-May-2016



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	1.2	4.75
1500	7.6	2.3	3.3
2000	8.9	3.5	2.54
2500	10.9	5.1	2.14
3000	19.4	6.6	2.94
3500	27	8.5	3.18
4000	32.2	10.9	2.95
4500	36.3	13.6	2.67
5000	40.5	15.7	2.58
5500	44.6	20	2.23
6000	48.7	23.6	2.06

0-20 MPH: 4.53

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.