

Boat Manufactured By:



124 Spaniel Lane • Summerville, SC 29483
 (410) 643-4141
www.avonmarine.com

GT 670

Length	22' 0"
Beam	8' 4"
Dry Weight (Boat Mfr. Pub)	1,941 lbs
Maximum HP	250 hp
Fuel Capacity	53 gal
Weight as Tested	3,463 lbs

F115LB / F115LB

Horsepower	115 hp
Induction	EFI
Displacement	1.8L
Weight (Estimated)	377 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

PROPELLER(S)

Series	Talon SS
Diameter x Pitch	13-1/8 x 18
Yamaha Part #	6N7-45974-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 75° F
Elevation (in feet above sea level)	0"
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 2 people, 2 batteries, safety and test equipment.

YPB#: PB_AVN_GT670_t_F115B_18Talon_2-15-18_INF



Engine: Yamaha F115LB / F115LB

Boat: GT 670

Configuration: Twin

Test Date: 15-Feb-2018



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	1.0	4.65
1500	6.6	1.8	3.67
2000	8.2	2.9	2.86
2500	13.3	4.2	3.17
3000	20.9	5.2	4.01
3500	26.2	6.6	3.97
4000	31.1	8.4	3.70
4500	34.9	10.2	3.43
5000	39.3	12.9	3.05
5500	43.3	15.9	2.73
6000	47.0	19.7	2.39
6300	49.3	21.8	2.26

Time to Plane: 2.28 sec. / 0-30 MPH: 3.89 sec.

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.