

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

{0:(903) 984-0541}

www.skeeterboats.com

Skeeter - Skeeter® Solera 189

SKEETER® SOLERA 189

Length	18' 9"
Beam	8' 4"
Dry Weight (Boat Mfr. Pub)	2,300 lbs
Maximum HP	175 hp
Fuel Capacity	34 gal
Weight as Tested	3,614 lbs

VF150XA V MAX SHO®

Horsepower	150 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68F-45978-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	56° F / 74° F
Elevation (in feet above sea level)	338'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 33 gallons of fuel, 3 batteries, bow-mounted trolling motor, bimini top up but stowed, safety and test gear.

YPB#: PB_SKT_Solera189_VF150XA_2016-11-19_WLY

Engine: Yamaha VF150XA V MAX

SHO®

Boat: Skeeter® Solera 189

Configuration: Single

Test Date: 19-Nov-2016



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.8	0.7	6.79
1500	6.0	1.2	4.96
2000	7.3	2.1	3.54
2500	8.1	3.3	2.46
3000	12.7	4.2	3.01
3500	24.9	4.7	5.30
4000	30.1	6.2	4.86
4500	34.9	8.5	4.13
5000	39.2	10.5	3.73
5500	44.0	14.0	3.14
6100	47.2	16.4	2.88
Time to Plane: 5.01 seconds
 0-30 MPH: 7.04 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.