

Boat Manufactured By:



300 Woodside Drive • St. Louis, MI 48880

(989) 681-4300

www.anglerqwestpontoon.com



QWEST® LS 820 XRE CRUISE

Length	21' 4"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	1,900 lbs
Maximum HP	150 hp
Fuel Capacity	12 gal
Pontoon # / Diameter	3 / Q3
Weight as Tested	2,924 lbs

F150LA

Horsepower	150 hp
Induction	EFI
Displacement	2.7 L
Weight (Estimated)	480 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series-SDS™
Diameter x Pitch	14 1/4 x 17
Yamaha Part #	68F-45972-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	71° F / 56° F
Elevation (in feet above sea level)	825'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 6 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_QWE_LS820XREcruise_F150LA_2013-05-21_PNT

Engine: Yamaha F150LA

Boat: Qwest® LS 820 XRE Cruise

Configuration: Single

Test Date: 21-May-2013

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.2	0.7	6
1500	6.3	1.2	5.25
2000	8.2	1.8	4.56
2500	13	2.6	5
3000	17.5	3.5	5
3500	22.4	4.8	4.67
4000	27.6	6.1	4.53
4500	32.2	7.8	4.13
5000	36.5	9.8	3.73
5500	40.1	12.7	3.16
6000	43.3	15.5	2.79
0-30 MPH: 6.52
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.