

Boat Manufactured By:


199 Extrusion Place • Hot Springs, AR

(501) 262-5300

www.xpressboats.com

XPRESS® H 18 BAY

Length	18' 0"
Beam	7' 11"
Dry Weight (Boat Mfr. Pub)	1,187 lbs
Maximum HP	115 hp
Fuel Capacity	18 gal
Weight as Tested	2,193 lbs

VF115LA V MAX SHO®

Horsepower	115 hp
Induction	EFI
Displacement	111.8 cu. in.
Weight (Estimated)	377 lbs
Gear Ratio	2.15

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Performance 3
Diameter x Pitch	13 1/4 x 18
Yamaha Part #	MAR-GYT3B-V4-18
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	65° F / 60° F
Elevation (in feet above sea level)	300'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 1 battery, bow-mounted trolling motor, safety and test gear.

YPB#: PB_XPR_H18Bay_VF115LA_2016-03-21_ALM

Engine: Yamaha VF115LA V MAX

VF115LA V MAX SHO®

SHO®

Boat: Xpress® H 18 Bay

Configuration: Single

Test Date: 21-Mar-2016

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.3	0.6	7.17
1500	6	1	6
2000	7	1.4	5
2500	10.4	2.2	4.73
3000	19	2.7	7.04
3500	24.6	3.7	6.65
4000	28.4	4.7	6.04
4500	32.7	5.7	5.74
5000	38.1	7.5	5.08
5500	43.2	9.8	4.41
6000	47.3	12.1	3.91
6250	48	12.1	3.97
Time to Plane : 3.59
 0-30 MPH : 6.44			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.