

Boat Manufactured By:



1392 Rimmel Dam Rd. • Malvern, AR 72104

(501) 566-1525

www.verandamarine.com

VERANDA® VR25L

Length	25' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,400 lbs
Maximum HP	250 hp
Fuel Capacity	40 gal
Pontoon # / Diameter	3 / 25"
Weight as Tested	4,512 lbs

F200LB

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	487 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/2 x 15
Yamaha Part #	68F-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	82° F / 80° F
Elevation (in feet above sea level)	297'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 25 gallons of fuel, 1 battery, bimini top up but stowed, safety and test gear.

YPB#: PB_VER_VR25L_F200LB_2017-08-29_PNT



Engine: Yamaha F200LB

Boat: Veranda® VR25L

Configuration: Single

Test Date: 29-Aug-2017



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.3	0.8	5.38
1500	6.1	1.2	5.08
2000	8.1	1.8	4.50
2500	11.4	2.6	4.39
3000	17.0	3.3	5.15
3500	20.8	4.2	4.95
4000	24.5	6.0	4.08
4500	28.1	7.6	3.70
5000	31.9	10.8	2.95
5500	35.6	14.3	2.49
6100	40.4	18.9	2.14
0-20: 3.82
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.