



41146 Schafer Rd. • Los Fresnos, TX 78566
 (956) 233-9489
www.shallowsportboats.com



SHALLOW SPORT 25 X3

Length	25' 5"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	2,500 lbs
Maximum HP	425 hp
Fuel Capacity	80 gal
Weight as Tested	4,444 lbs

F300XSB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	611 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Anti-Ventilation Plate Height	10" Hydraulic Plate

PROPELLER(S)

Series	Aftermarket 4 Blade
Diameter x Pitch	14-1/2 x 18
Yamaha Part #	N/A
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	82° F / 74° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 4 batteries, charger, bow mounted trolling motor, upper station T-top, safety and test equipment.

YPB#: PB_ShallowSport_25X3_F300XSB2_02-19-22_BAY

Engine: Yamaha F300XSB2

Boat: Shallow Sport 25 X3

Configuration: Single

Test Date: 19-Feb-0202



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.4	3.57
1500	6.4	2.4	2.72
2000	8.4	4.3	1.95
2500	12.1	5.7	2.12
3000	14.8	6.9	2.14
3500	23.9	9.5	2.53
4000	29.8	13.7	2.18
4500	33.9	19.7	1.72
5000	42.7	25.5	1.68
5500	46.5	25.6	1.75
5800	48.0	26.8	1.79
0-20 MPH: 6.64 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.