

Boat Manufactured By:

Hurricane

4310 Middlebury St. • Elkhart, IN 46516

(574) 522-8381

www.hurricaneboats.com



HURRICANE® SUNDECK SPORT 192 RL OB

Length	18' 10"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	2,450 lbs
Maximum HP	200 hp
Fuel Capacity	36 gal
Weight as Tested	3,578 lbs

VF115XA V MAX SHO®

Horsepower	115 hp
Induction	EFI
Displacement	111.8 cu in
Weight (Estimated)	386 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Talon GP™
Diameter x Pitch	13 1/2 x 15
Yamaha Part #	6FP-45943-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	76° F / 74° F
Elevation (in feet above sea level)	840'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 34 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_HUR_SunDeckSport192RLOB_VF115XA_2017-08-28_DCK

Engine: Yamaha VF115XA V MAX SHO®

Boat: Hurricane® SunDeck Sport 192 RL OB

Configuration: Single

Test Date: 28-Aug-2017



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.9	0.5	7.80
1500	5.5	0.8	6.88
2000	6.7	1.2	5.58
2500	7.6	1.9	4.00
3000	8.5	3.0	2.83
3500	12.0	4.1	2.93
4000	20.6	4.3	4.79
4500	25.6	4.9	5.23
5000	29.1	6.2	4.69
5500	32.8	8.3	3.95
6000	35.2	10.2	3.45
6300	38.5	12.2	3.16
0-20 MPH: 6.80
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.