

Boat Manufactured By:



901 Cowan Drive • Lebanon, MO 65536
(417) 588-9787
www.g3boats.com



G3 BOATS® 15 DLX

Length	15' 5"
Beam	5' 9"
Dry Weight (Boat Mfr. Pub)	500 lbs
Maximum HP	40 hp
Weight as Tested	1,280 lbs

F40LA

Horsepower	40 hp
Induction	EFI
Displacement	45.7 cu. in.
Weight (Estimated)	214 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Aluminum
Diameter x Pitch	11 5/8 x 11
Yamaha Part #	69W-45947-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 87° F
Elevation (in feet above sea level)	918'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 5 gallons of fuel, 2 batteries, Yamaha F40 Tiller Handle, bow-mounted trolling motor, safety and test gear.

YPB#: PB_G3B_15DLX_F40LA_2017-07-14_ALM

Engine: Yamaha F40LA

Boat: G3 Boats® 15 DLX

Configuration: Single

Test Date: 14-Jul-2017



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.4	0.2	17
1500	4.7	0.4	11.75
2000	6	0.6	10
2500	7.1	0.8	8.88
3000	9.8	1.1	8.91
3500	14.1	1.4	10.07
4000	18.4	1.5	12.27
4500	21.4	2	10.7
5000	24.2	2.3	10.52
5500	26.7	3	8.9
5900	29.1	4.1	7.1
0-20 MPH: 4.21			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.