

Boat Manufactured By:



901 Cowan Drive • Lebanon, MO 65536
(417) 588-9787
www.g3boats.com

G3 ELITE 326 SS DLX

Length	26' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,340 lbs
Maximum HP	350 hp
Fuel Capacity	46 gal
Pontoon # / Diameter	3/23"x25"
Weight as Tested	4,745 lbs

F350XSA

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	92° F / 87° F
Elevation (in feet above sea level)	867'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 46 gallons of fuel, 2 batteries, 2 people, Bimini top up and stowed, safety and test equipment.

YPB#: PB_G3B_Elite 326SS DLX_F350XSA_06/19/24_PNT



Engine: Yamaha F350XSA

Boat: G3 Elite 326 SS DLX

Configuration: Single

Test Date: 19-Jun-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.3	1.2	4.53
1500	7.3	1.9	3.76
2000	10.7	3.1	3.50
2500	17.0	4.5	3.73
3000	21.9	6.4	3.44
3500	26.8	8.3	3.21
4000	31.8	11.1	2.87
4500	36.5	14.2	2.57
5000	41.5	18.0	2.30
5500	46.9	22.5	2.08
6000	51.5	29.3	1.76
0-20 MPH: 3.98 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.