

Boat Manufactured By:



7800 Northport Drive • Lansing, MI 48917
 (517) 322-3822
www.manitoupontoonboats.com

MANITOU 20 OASIS ANGLER SHP

Length	20' 11"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,540 lbs
Maximum HP	175 hp
Fuel Capacity	44 gal
Pontoons Diameter	3 / SHP
Weight as Tested	3,664 lbs

VF150LA

Horsepower	150 hp
Induction	EFI
Displacement	2.8L
Weight (Estimated)	480 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/2 x 15
Yamaha Part #	68F-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	74° F / 71° F
Elevation (in feet above sea level)	850'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 22 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_MAN_20OasisAnglerSHP_VF150LA_2013-10-03_PNT



Engine: Yamaha VF150LA

Boat: Manitou 20 Oasis Angler SHP

Configuration: Single

Test Date: 2-Oct-2013



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.2	0.7	6.00
1500	5.9	1.2	4.92
2000	7.6	1.8	4.22
2500	11.9	2.8	4.25
3000	16.2	3.6	4.50
3500	21.0	4.8	4.38
4000	25.6	6.2	4.13
4500	30.9	8.3	3.72
5000	34.4	10.1	3.41
5500	38.3	12.7	3.02
6000	42.7	15.4	2.77
0-30 MPH: 6.58 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.