

Boat Manufactured By:
SEA FOX
BOAT WORKS
 2550 Highway 52 • Moncks Corner, SC
 (843) 761-6090
 www.seafoxboats.com

Sea Fox® - Sea Fox® 266 Commander

SEA FOX® 266 COMMANDER

Length	26' 0"
Beam	9' 3"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	400 hp
Fuel Capacity	143 gal
Weight as Tested	5,694 lbs

F150XCA / LF150XCA

Horsepower	150 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	487 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/4 x 18
Yamaha Part #	68F-45978-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 81° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 2 batteries, safety and test gear.

YPB#: PB_SF_X_266Commander_t_F150XCA_2017-08-13_OCC

Engine: Yamaha F150XCA / LF150XCA

Boat: Sea Fox® 266 Commander

Configuration: Twin

Test Date: 13-Aug-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	1.7	3.06
1500	7.2	2.6	2.77
2000	8.6	4.6	1.87
2500	11	6.4	1.72
3000	19.2	7.6	2.53
3500	26.1	10.1	2.58
4000	31.5	12.2	2.58
4500	36.4	15.5	2.35
5000	41	20.3	2.02
5500	45.5	25.7	1.77
6000	49	30.9	1.59
0-30 MPH: 4.95
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.