

Boat Manufactured By:



300 West Chicago Street • Syracuse, IN 46567
 (574) 457-5731
 www.larsonfx.com

LARSON FX® 1750 TL

Length	17' 5"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	1,600 lbs
Maximum HP	90 hp
Fuel Capacity	22 gal
Weight as Tested	2,725 lbs

F90XA

Horsepower	90 hp
Induction	EFI
Displacement	97 cu. in.
Weight (Estimated)	366 lbs
Gear Ratio	2.27

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Aluminum "K" Series
Diameter x Pitch	13 1/4 x 17
Yamaha Part #	6E5-45945-01-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	72° F / 74° F
Elevation (in feet above sea level)	1290'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 15 gallons of fuel, 4 batteries, safety and test gear.

YPB#: PB_LFX_1750TL_F90XA_2014-07-31_WLY



Engine: Yamaha F90XA

F90XA

Boat: Larson FX® 1750 TL

Configuration: Single

Test Date: 31-Jul-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.2	0.4	8
1500	4.7	0.7	6.71
2000	6	1.1	5.46
2500	7.1	1.9	3.74
3000	8.1	2.8	2.89
3500	10.7	3.6	2.97
4000	21.4	3.8	5.63
4500	25.9	4.7	5.51
5000	29.8	5.8	5.14
5500	33.4	7.1	4.7
6000	36.8	9	4.09
0-20 MPH: 7.33
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.