



Boat Manufactured By:
2550 Highway 52 • Moncks Corner, SC
(843) 761-6090
www.seafoxboats.com

SEA FOX 268 TRAVELER

Length	26' 0"
Beam	9' 3"
Dry Weight (Boat Mfr. Pub)	6,200 lbs
Maximum HP	425 hp
Fuel Capacity	127 gal
Weight as Tested	8,288 lbs

F200XB / LF200XB

Horsepower	200 hp
Induction	EFI/DOHC
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68F-45978-20-00 / 68G-45978-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	45° F / 55° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 4 batteries, safety and test equipment.

YPB#: PB_SFX_268 Traveler_TW_LF200XB_12-9-2021_ODC



Engine: Yamaha F200XB / LF200XB

Boat: Sea Fox 268 Traveler

Configuration: Twin

Test Date: 9-Dec-2021



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	1.8	3.20
1500	7.3	2.8	2.61
2000	9.3	5.1	1.83
2500	12.5	6.6	1.91
3000	21.5	8.3	2.59
3500	27.6	10.2	2.72
4000	33.3	13.5	2.46
4500	39.0	18.5	2.11
5000	42.7	24.6	1.73
5500	46.7	31.8	1.47
6000	51.3	38.9	1.32
Time to Plane: 4.00 seconds 0-30 MPH: 6.55 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.