

Boat Manufactured By:



2300 Jetport Drive • Orlando, FL 32809

(407) 851-7951

www.regalboats.com

REGAL® 29 OBX

Length	29' 1"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	6,550 lbs
Maximum HP	400 hp
Fuel Capacity	73 gal
Weight as Tested	9,146 lbs

F200XB / LF200XB

Horsepower	200 hp
Induction	EFI
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68F-45978-10-00 / 68G-45978-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	79° F / 85° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes full tank of fuel, 3 batteries, fresh water system, power assist steering, arch, safety and test gear.

YPB#: PB_RGL_29OBX_t_F200XB_2016-09-26_RBT



Engine: Yamaha F200XB / LF200XB

Boat: Regal® 29 OBX

Configuration: Twin

Test Date: 26-Sep-2016

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.9	1.6	3.13
1500	7.0	2.6	2.75
2000	8.2	4.3	1.91
2500	8.9	6.9	1.30
3000	12.2	10.0	1.22
3500	24.1	11.7	2.06
4000	31.1	14.6	2.14
4500	36.5	19.6	1.86
5000	41.5	25.6	1.62
5500	46.2	33.4	1.39
6100	50.6	40.3	1.26
0-30 MPH: 10.93 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.