

# PERFORMANCE BULLETIN

Boat Manufactured By:



{0:(574) 457-2082}

# www.polarkraft.com

# **POLAR KRAFT® KODIAK V 165 SC®**

Length	16' 4"
Beam	6' 8"
Dry Weight (Boat Mfr. Pub)	912 lbs
Maximum HP	75 hp
Fuel Capacity	18 gal
Weight as Tested	1,782 lbs

## F50TLR

Horsepower	50 hp
Displacement	60.8 cu. in.
Weight (Estimated)	247 lbs
Gear Ratio	1.85

#### **ENGINE MOUNTING HEIGHT**

Mounting Hole Position	#1
------------------------	----

# PROPELLER(S)

Series	Aluminum Series
Diameter x Pitch	10 5/8 x 12
Yamaha Part #	6H5-45952-00-00
Propeller Material	Aluminum

## **TEST CONDITIONS**

Number of People	2
Air / Water Temperature	72° F / 65° F
(Fahrenheit)	72 F 7 05 F
Elevation (in feet above sea level)	840'
Wind Velocity	5-10 MPH

# **COMMENTS**

Test weight includes full tank of fuel, 1 battery, bow-mounted trolling motor, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-20 speed data gathered with aftermarket speedometer. Other speed data gathered with GPS receiver.

YPB#: PB\_PLK\_KodiakV165SC\_F50TLR\_2011-06-29\_ALM



F50TLR

Engine: Yamaha F50TLR

Boat: Polar Kraft® Kodiak V 165 SC®

**Configuration:** Single Test Date: 29-Jun-2011

#### **PERFORMANCE DATA**

RPM	MPH	GPH	MPG
1000	3.3	0.3	11
1500	4.5	0.6	7.5
2000	5.8	0.9	6.44
2500	6.8	1.2	5.67
3000	8.1	1.7	4.77
3500	13.2	1.9	6.95
4000	18.8	2.3	8.17
4500	22.5	2.7	8.33
5000	26	3.4	7.65
5500	29.1	4.4	6.61
5700	31	4.6	6.74
Seconds 0-20 MPI	1· 8 2/hr />		

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity elevation, bottom paint, boat options affecting wind/water drag and/or boat weight and operator ability. Please confirm the specifications and performance data on your specific boatlengine combination with your deler prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using variable PowerAsted components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.