

Boat Manufactured By:



103 Blanchard Avenue • Mountain View, AR 72560
(870) 269-9000
www.excelboats.net

EXCEL® BAY PRO 183

Length	18' 3"
Beam	7' 11"
Dry Weight (Boat Mfr. Pub)	1,350 lbs
Maximum HP	115 hp
Fuel Capacity	18 gal
Weight as Tested	2,387 lbs

VF115LA V MAX SHO®

Horsepower	115 hp
Induction	EFI
Displacement	111.8 cu. in.
Weight (Estimated)	377 lbs
Gear Ratio	2.15

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2 on Manual Jack Plate
Ventilation Plate Height	2 3/4" Above Boat Bottom

PROPELLER(S)

Series	Talon SS™
Diameter x Pitch	13 1/8 x 20
Yamaha Part #	6N7-45978-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	68° F / 60° F
Elevation (in feet above sea level)	450'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 16 gallons of fuel, 3 batteries, 6" manual jack plate, safety and test gear.

YPB#: PB_EXL_BayPro183_VF115LA_2015-04-22_ALM



Engine: Yamaha VF115LA V MAX SHO®

Boat: Excel® Bay Pro 183

Configuration: Single

Test Date: 22-Apr-2015

VF115LA V MAX SHO®

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.3	0.5	8.6
1500	6	1	6
2000	7.4	1.7	4.35
2500	12.1	2.5	4.84
3000	22.1	3	7.37
3500	27.6	3.7	7.46
4000	32.3	4.9	6.59
4500	37	5.7	6.49
5000	41.9	8.5	4.93
5500	46.6	10.4	4.48
6000	48.6	11.3	4.3
6200	50.1	11.9	4.21
0-20 MPH: 6.05
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.