



41146 Schafer Rd. • Los Fresnos, TX 78566
 (956) 233-9489
 www.shallowportboats.com



SHALLOW SPORT 25 X3

Length	25' 2"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	2,500 lbs
Maximum HP	425 hp
Fuel Capacity	80 gal
Weight as Tested	4,547 lbs

XF425XSA

Horsepower	425 hp
Induction	DI/VCT/DOHC
Displacement	5.6L
Weight (Estimated)	952 lbs
Gear Ratio	1.79:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	XTO Offshore
Diameter x Pitch	16-3/8 x 20
Yamaha Part #	6GR-45936-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	83° F / 74° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 4 batteries, 36 volt trolling motor, 10" jack plate, safety and test equipment.

YPB#: PB_SHS_25X3_XF425XSA_02-12-20_BAY

Engine: Yamaha XF425XSA

Boat: Shallow Sport 25 X3

Configuration: Single

Test Date: 12-Feb-2020

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.9	2.0	2.49
1500	7.1	2.9	2.47
2000	8.7	4.6	1.88
2500	12.6	6.8	1.85
3000	23.8	8.1	2.92
3500	29.3	11.5	2.55
4000	33.8	15.2	2.23
4500	38.9	20.1	1.94
5000	44.8	26.2	1.71
5500	51.0	33.6	1.50
6150	57.3	37.1	1.54

Time to Plane: 4.52 seconds
 0-20 MPH: 5.28 seconds

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.