

Boat Manufactured By:



ALBEMARLE 30 EXPRESS

Length	30' 10"
Beam	10' 6"
Dry Weight (Boat Mfr. Pub)	11,300 lbs
Maximum HP	900 hp
Fuel Capacity	320 gal
Weight as Tested	15,188 lbs

F300XCA / F300ECA / LF300XCA

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	562 - 588 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3-1/4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series 11™
Diameter x Pitch	15 x 20
Yamaha Part #	6CE-45932-20-00 / 6CE-45932-20-00 / 6CF-45932-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	45° F / 50° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 200 gallons of fuel, 4 batteries, safety and test equipment.

YPB#: PB_ALB_30EXPRESS_TR_F300_12-18-2020_OCC



Engine: Yamaha F300XCA / F300ECA / LF300XCA

Boat: Albemarle 30 Express

Configuration: Triple

Test Date: 18-Dec-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.9	4.1	1.69
1500	8.9	6.7	1.33
2000	10.6	11.6	0.91
2500	14.0	17.6	0.79
3000	18.5	23.3	0.79
3500	31.9	27.8	1.15
4000	39.0	36.6	1.07
4500	43.8	46.3	0.95
5000	49.4	57.4	0.86
5500	54.5	72.5	0.75
5900	60.2	81.2	0.74
0-30 MPH: 6.35 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.