

Boat Manufactured By:



P.O. Box 1380 • Lexington, SC
(803) 755-6539
www.seahuntboats.com



SEA HUNT ESCAPE 27

Length	27' 4"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	5,100 lbs
Maximum HP	425 hp
Fuel Capacity	144 gal
Weight as Tested	7,120 lbs

F200XCA

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	489 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	13-3/4 x 19
Yamaha Part #	68F-45974-20-00 / 68G-45974-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	45° F / 53° F
Elevation (in feet above sea level)	250'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 80 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_SHT_Escape27_TW_F200XCA_1-14-2021_OCC

Engine: Yamaha F200XCA

Boat: Sea Hunt Escape 27

Configuration: Twin

Test Date: 14-Jan-2021



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	1.6	3.56
1500	8.1	2.7	3.00
2000	9.6	4.7	2.04
2500	15.6	6.9	2.26
3000	22.3	8.3	2.69
3500	29.6	10.7	2.77
4000	35.2	15.1	2.33
4500	40.8	19.4	2.10
5000	45.3	26.9	1.68
5500	50.3	36.5	1.38
5900	53.1	38.3	1.39

Time to Plane: 4.05 seconds / **0-30 MPH: 6.60 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.