

Boat Manufactured By:

Hurricane

4310 Middlebury St. • Elkhart, IN 46516

(574) 522-8381

www.hurricaneboats.com



HURRICANE FUNDECK 2360 SBC

Length	23' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,350 lbs
Maximum HP	250 hp
Fuel Capacity	48 gal
Weight as Tested	4,636 lbs

F250XB

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	551 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CE-45976-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	74° F / 72° F
Elevation (in feet above sea level)	780'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_HUR_FunDeck 2360 SBC_F250XB_8-31-2021_DCK

Engine: Yamaha F250XB

Boat: Hurricane FunDeck 2360 SBC

Configuration: Single

Test Date: 30-Aug-2021



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.2	4.17
1500	7.5	2.0	3.75
2000	9.4	3.2	2.94
2500	16.3	4.6	3.54
3000	22.4	6.2	3.61
3500	27.0	7.6	3.55
4000	31.0	10.4	2.98
4500	35.2	13.2	2.67
5000	38.3	16.8	2.28
5500	42.4	20.4	2.08
6000	45.5	23.9	1.90
0-20 MPH: 3.38 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.