

Boat Manufactured By:

BULLET

TOTAL PERFORMANCE BOATS

PO Box 2202 • Knoxville, TN 37901
(865) 577-7055
www.bulletboats.com

BULLET® 21SS

Length	21' 0"
Beam	7' 7"
Dry Weight (Boat Mfr. Pub)	1,300 lbs
Maximum HP	300 hp
Fuel Capacity	36 gal
Weight as Tested	2,512 lbs

VF250LA

Horsepower	250 hp
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2 on 10" Hydraulic Jack Plate
Ventilation Plate Height	8 7/8" Above Boat Bottom

PROPELLER(S)

Series	Non-Yamaha 4-Blade
Diameter x Pitch	15 1/4 x 29
Yamaha Part #	Non-Yamaha
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 77° F
Elevation (in feet above sea level)	682'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 3 batteries, bow-mount trolling motor, 10" hydraulic jack plate, safety and test gear.

YPB#: PB_BUL_21SS_VF250LA_2012-10-10_BSS



Engine: Yamaha VF250LA

Boat: Bullet® 21SS

Configuration: Single

Test Date: 10-Oct-2012

VF250LA

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.9	1.5	3.93
1500	7	2.9	2.41
2000	8	4.1	1.95
2500	26.4	5	5.28
3000	33.8	6.2	5.45
3500	42.3	8.8	4.81
4000	51.2	10.1	5.07
4500	61.2	14.5	4.22
5000	68.5	16.1	4.26
5500	76.8	20.1	3.82
6000	85	23.2	3.66
0-30 MPH: 4.65
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.