

Boat Manufactured By:

Bentley Pontoons Logo

 1650 Two Notch Rd. • Lexington, SC 29073
 (803) 391-3000

www.bentleypontoons.com

BENTLEY 243 FISH N CRUISE

Length	24' 8"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,120 lbs
Maximum HP	250 hp
Fuel Capacity	32 gal
Pontoon # / Diameter	2.75 / 25"
Weight as Tested	3,203 lbs

F150XB

Horsepower	150 hp
Induction	EFI/DOHC
Displacement	2.7L
Weight (Estimated)	489 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	2" Above Boat Bottom

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/2 x 15
Yamaha Part #	68F-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	89° F / 84° F
Elevation (in feet above sea level)	250'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 16 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_BEN_243Fish_N_Cruise_F150XB_8-12-2020_PNT

Engine: Yamaha F150XB

Boat: Bentley 243 Fish N Cruise

Configuration: Single

Test Date: 11-Aug-2020


PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.1	0.7	5.86
1500	5.6	1.2	4.63
2000	8.0	1.8	4.57
2500	10.9	2.6	4.25
3000	16.1	3.5	4.59
3500	19.8	4.8	4.16
4000	24.1	6.3	3.86
4500	29.0	8.0	3.63
5000	33.1	9.5	3.50
5500	36.9	12.3	3.00
6100	41.2	15.6	2.65
0-20 MPH: 4.37 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.