

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

{0:(903) 984-0541}

www.skeeterboats.com

SKEETER® ZX 200

Length	19' 6"
Beam	7' 11"
Dry Weight (Boat Mfr. Pub)	2,075 lbs
Maximum HP	200 hp
Fuel Capacity	36 gal
Weight as Tested	3,357 lbs

VF200LA V MAX SHO®

Horsepower	200 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Jack Plate	12" Manual

PROPELLER(S)

Series	V MAX SHO®
Diameter x Pitch	15 1/8" x 23
Yamaha Part #	6CB-45974-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	99° F / 90° F
Elevation (in feet above sea level)	340'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 18 gallons of fuel, 3 batteries, bow-mount trolling motor, 3-bank battery charger, 12" manual jack plate, safety and test gear.

YPB#: PB_SKT_ZX200_VF200LA_2015-08-04_BSS



Engine: Yamaha VF200LA V MAX

VF200LA V MAX SHO®

SHO®

Boat: Skeeter® ZX 200

Configuration: Single

Test Date: 4-Aug-2015

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	1.5	3.73
1500	7.3	2.8	2.61
2000	8.4	4	2.1
2500	11.5	5.7	2.02
3000	32.2	7	4.6
3500	37.6	9.4	4
4000	43.5	12.4	3.51
4500	50	14.8	3.38
5000	57.6	16.5	3.49
5500	63.6	18.7	3.4
5900	67.2	19.1	3.52
0-30 MPH: 7.17			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.