

Boat Manufactured By:

 3101 South US Highway 1 • Fort Pierce, Florida 34982
 (772) 429-2525
twinvee.com

TWIN VEE 260 GFX2

Length	26' 0"
Beam	8' 8"
Dry Weight (Boat Mfr. Pub)	5,880 lbs
Maximum HP	400 hp
Fuel Capacity	191 gal
Weight as Tested	7,500 lbs

LF200XSA2 / F200XSA2

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	525 - 525 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Reliance
Diameter x Pitch	14-1/4 x 17
Yamaha Part #	68G-45972-20-00 / 68F-45972-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	5
Air / Water Temperature (Fahrenheit)	88° F / 85° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_TWN_260GFX2_TW_LF200XSA2_06-17-2024_CAT



Engine: Yamaha LF200XSA2 / F200XSA2

Boat: Twin Vee 260 GFX2

Configuration: 21

Test Date: 17-Jun-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.4	1.7	2.56
1500	5.9	2.8	2.13
2000	7.8	4.5	1.72
2500	8.8	7.1	1.25
3000	15.6	9.5	1.65
3500	24.1	12.1	2.00
4000	29.0	14.8	1.96
4500	33.2	19.1	1.74
5000	37.9	25.1	1.51
5500	41.6	32.4	1.29
6000	45.7	41.5	1.10
0-20 MPH: 5.14 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.