

Boat Manufactured By:



ALBEMARLE 25 EXPRESS

Length	27' 2"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	6,400 lbs
Maximum HP	500 hp
Fuel Capacity	190 gal
Weight as Tested	8,284 lbs

F250XCA / LF250XCA

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	562 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3-1/2" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series 11™
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00 / 6CF-45934-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	90° F / 88° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 130 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_ALB_25EXPRESS_TW_F250XCA_09-03-20_OCC

Engine: Yamaha F250XCA / LF250XCA

Boat: Albemarle 25 Express

Configuration: Twin

Test Date: 1-Sep-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.3	2.5	2.57
1500	8.2	4.0	2.05
2000	9.7	7.2	1.36
2500	11.9	10.6	1.12
3000	15.5	13.8	1.12
3500	29.0	16.9	1.72
4000	35.5	23.0	1.55
4500	40.6	28.6	1.42
5000	45.2	37.7	1.20
5500	49.3	45.3	1.09
5900	53.2	49.2	1.08
0-30 MPH: 6.58 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.