

Boat Manufactured By:



JEANNEAU NC 1295 FLY

Length	41' 2"
Beam	12' 6"
Dry Weight (Boat Mfr. Pub)	18,036 lbs
Maximum HP	900 hp
Fuel Capacity	310 gal
Weight as Tested	22,544 lbs

LF300XSB2 / F300USB2 / F300XSB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	611 - 624 - 611 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CF-45976-20-00 / 6CE-45976-20-00 / 6CE-45976-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	80° F / 74° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 235 gallons of fuel, 5 batteries, Fischer Panda 8000i Generator, safety and test equipment.

YPB#: PB_JEA_NC 1295 Fly_TR_F300USB2_7-14-2025_OWA

Engine: Yamaha LF300XSB2 / F300USB2 / F300XSB2

Boat: Jeanneau NC 1295 Fly

Configuration: Triple

Test Date: 14-Jul-2025



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	3.9	1.35
1500	7.6	5.8	1.30
2000	10.1	11.9	0.84
2500	10.7	15.9	0.68
3000	11.6	18.1	0.64
3500	18.9	23.1	0.82
4000	25.9	33.2	0.78
4500	32.0	41.5	0.77
5000	36.5	50.5	0.72
5500	40.7	62.6	0.65
6000	44.8	78.3	0.57
0 - 20 MPH: 5.95 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.