

Boat Manufactured By:



210 Industrial Boulevard • Tullahoma, TN

(931) 455-2014

www.phoenixbassboats.com

PHOENIX® 618 PRO

Length	18' 6"
Beam	7' 10"
Dry Weight (Boat Mfr. Pub)	1,500 lbs
Maximum HP	175 hp
Fuel Capacity	36 gal
Weight as Tested	2,848 lbs

VF175LA V MAX SHO®

Horsepower	175 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	480 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4 on Manual Jack Plate
Ventilation Plate Height	6" Above Boat Bottom

PROPELLER(S)

Series	Turbo FXP Series
Diameter x Pitch	14 3/4 x 22
Yamaha Part #	MAR-14722-R1-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	67° F / 73° F
Elevation (in feet above sea level)	607'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 3 batteries, bow-mounted trolling motor, 2-bank onboard battery charger, 10" manual jack plate, safety and test gear.

YPB#: PB_PHX_618Pro_VF175LA_2014-10-02_BSS



Engine: Yamaha VF175LA V MAX SHO®

VF175LA V MAX SHO®

Boat: Phoenix® 618 Pro

Configuration: Single

Test Date: 2-Oct-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	0.9	5.78
1500	6.8	1.8	3.78
2000	8	3.1	2.58
2500	24.7	3.6	6.86
3000	30.3	4.8	6.31
3500	36.3	6.7	5.42
4000	42.5	8.3	5.12
4500	48	9.6	5
5000	53.6	13.5	3.97
5500	58.7	15.1	3.89
6050	64.5	19.7	3.27
0-30 MPH: 8.97			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.