



Engine: Yamaha F350XSA2 / LF350XSA2
Boat: Sportsman Open 302
Configuration: Twin
Test Date: 19-Jun-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.8	2.5	2.30
1500	8.3	4.5	1.87
2000	10.1	7.5	1.36
2500	13.7	11.9	1.15
3000	18.6	15.0	1.24
3500	31.6	18.3	1.73
4000	38.0	24.2	1.57
4500	43.5	30.1	1.45
5000	49.2	39.2	1.26
5500	54.7	53.8	1.02
5950	59.2	60.5	0.98

Time to Plane: 6.86 seconds
 0-30 MPH: 8.50 seconds

SPORTSMAN OPEN 302

Length	30' 2"
Beam	10' 4"
Dry Weight (Boat Mfr. Pub)	8,245 lbs
Maximum HP	700 hp
Fuel Capacity	295 gal
Weight as Tested	11,937 lbs

F350XSA2 / LF350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 - 629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
Ventilation Plate Height	3/4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 20
Yamaha Part #	6CF-45932-20-00 / 6CE-45932-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	82° F / 80° F
Elevation (in feet above sea level)	0'
Wind Velocity	15-20 MPH

COMMENTS

Test weight includes 150 gallons of fuel, 6 batteries, optional Sea Keeper 2, safety and test equipment.

YPB#: PB_SPT_Open 302_TW_F350XSA2_6-19-2024_OCC

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.