

PERFORMANCE BULLETIN

Boat Manufactured By: {0:(229) 377-2125}

www.southwindboats.com

SOUTHWIND® 2400 SD®

Length	25' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,722 lbs
Maximum HP	300 hp
Fuel Capacity	55 gal
Weight as Tested	5,855 lbs

F225XCA

Horsepower	225 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position #2

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 3/4 x 15
Yamaha Part #	6D0-45976-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature	91° F / 82° F
(Fahrenheit)	91 F/02 F
Elevation (in feet above sea level)	194'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes full tank of fuel, 2 batteries, ski tower with bimini top deployed, 6-person load, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with radar gun. Other speed data gathered with GPS receiver.

YPB#: PB_SWD_2400SD_F225XCA_2011-05-24_DCK



Engine: Yamaha F225XCA

Boat: SouthWind® 2400 SD® **Configuration:** Single Test Date: 24-May-2011

F225XCA

PERFORMANCE DATA

1000	5.3	1.2	4.42
1500	7.1	2.1	3.38
2000	8.3	3.2	2.59
2500	8.7	4.7	1.85
3000	9.5	6.4	1.48
3500	11.4	8.7	1.31
4000	29.7	9.4	3.16
4500	33.7	11.8	2.86
5000	38	14.5	2.62
5500	41.6	17.1	2.43
6100	46.4	21.7	2.14

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity elevation, bottom paint, boat options affecting wind/water drag and/or boat weight and operator ability. Please confirm the specifications and performance data on your specific boatlengine combination with your deler prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using variable PowerAsted components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.