

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

{0:(903) 984-0541}

www.skeeterboats.com

SKEETER® MX 1825

Length	18' 4"
Beam	8' 1"
Dry Weight (Boat Mfr. Pub)	2,075 lbs
Maximum HP	200 hp
Fuel Capacity	36 gal
Weight as Tested	3,435 lbs

VF150XA

Horsepower	150 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Reliance Series-SDS
Diameter x Pitch	13 3/4 x 19
Yamaha Part #	68F-45974-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	65° F / 74° F
Elevation (in feet above sea level)	605'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes full tank of fuel, 3 batteries, bow-mount trolling motor, 3-bank battery charger, safety and test gear.

YPB#: PB_SKT_MX1825_VF150XA_2014-10-01_WLY



Engine: Yamaha VF150XA

VF150XA

Boat: Skeeter® MX 1825

Configuration: Single

Test Date: 1-Oct-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.8	0.8	4.75
1500	6.5	1.3	5
2000	7.6	2.2	3.46
2500	9.1	3.6	2.53
3000	20.5	3.8	5.4
3500	27.1	4.8	5.65
4000	32.5	6.8	4.78
4500	37.9	8.7	4.36
5000	43.1	11.5	3.75
5500	48.4	15.5	3.12
5950	51	16.2	3.15
0-30 MPH: 7.53			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.