

Boat Manufactured By:



an Drive • Lebanon, MO 65536 901 Cov (417) 588-9787 www.g3boats.com

G3 BOATS® SPORTSMAN 19

Length	19' 10"
Beam	7' 8"
Dry Weight (Boat Mfr. Pub)	1,210 lbs
Maximum HP	150 hp
Fuel Capacity	21 gal
Weight as Tested	2,426 lbs

VF150LA V MAX SHO®

Horsepower	150 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	480 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
PROPELLER(S)	
Series	Painted Stainless
Diameter x Pitch	14 1/2 x 21

Diameter x Pitch	14 1/2 x 21
Yamaha Part #	61A-45972-00-00
Propeller Material	Painted Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	95° F / 88° F
Elevation (in feet above sea level) Wind Velocity	918' 0-5 MPH

COMMENTS

Test weight includes 21 gallons of fuel, 3 batteries, bow-mounted trolling motor, 8-foot Power-Pole, safety and test gear

YPB#: PB G3B Sportsman19 VF150LA 2017-07-10 ALM

PERFORMANCE BULLETIN



VF150LA V MAX SHO®

Engine: Yamaha VF150LA V MAX SHO® Boat: G3 Boats® Sportsman 19 Configuration: Single Test Date: 10-Jul-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	0.8	5.88
1500	6.6	1.4	4.71
2000	9.2	2.5	3.68
2500	19.6	3.2	6.13
3000	26.4	3.8	6.95
3500	31.5	5.1	6.18
4000	36.5	7.3	5
4500	41.3	9.1	4.54
5000	45.7	12	3.81
5500	51.3	15.4	3.33
5800	52.1	15.5	3.36

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.