

Boat Manufactured By:

TRIFECTA

51773 County Rd 39 N • Middlebury, IN 46540
{0:(574) 825-8696}
www.trifectapontoon.com

TRIFECTA S SERIES 23 RF 3.0

Length	24' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,450 lbs
Maximum HP	250 hp
Fuel Capacity	37 gal
Pontoons Diameter	3 / 3.0
Weight as Tested	3,654 lbs

VF200LB

Horsepower	200 hp
Induction	EFI/DOHC
Displacement	4.2L
Weight (Estimated)	525 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 3/4 x 13
Yamaha Part #	6CE-45930-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	75° F / 80° F
Elevation (in feet above sea level)	796'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 25 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_TRF_S Series 23RF 3.0_VF200LB_09-14-21_PNT



Engine: Yamaha VF200LB

Boat: Trifecta S Series 23 RF 3.0

Configuration: Single

Test Date: 13-Sep-2021



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.1	1.3	3.88
1500	7.0	2.1	3.41
2000	7.6	2.8	2.70
2500	8.8	3.6	2.43
3000	12.3	4.9	2.51
3500	23.1	7.9	2.92
4000	27.7	9.8	2.84
4500	31.9	13.0	2.45
5000	35.5	14.5	2.45
5500	39.4	18.5	2.14
6000	43.0	19.4	2.22
0-20 MPH: 4.57 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.