

Boat Manufactured By:

BERKSHIRE

51773 Country Road 39 North • Middlebury, IN 46540
 (574) 825-8696
www.berkshirepontoon.com



BERKSHIRE® 23RFX STS 3.0

Length	23' 7"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,600 lbs
Maximum HP	250 hp
Fuel Capacity	40 gal
Pontoon # / Diameter	3 / 25
Weight as Tested	4,022 lbs

VF250LA V MAX SHO®

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 1/2 x 16
Yamaha Part #	6CE-45938-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	85° F / 75° F
Elevation (in feet above sea level)	675'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 35 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_BRK_23RFXSTS30_VF250LA_2016-07-19_PNT

Engine: Yamaha VF250LA V MAX SHO®

Boat: Berkshire® 23RFX STS 3.0

Configuration: Single

Test Date: 19-Jul-2016



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.3	4.23
1500	7.6	2.1	3.62
2000	8.1	2.9	2.79
2500	11.3	4.1	2.76
3000	17	5.1	3.33
3500	20.4	7.2	2.83
4000	25.1	9.6	2.62
4500	35.2	14	2.51
5000	38.8	16	2.43
5500	42.8	20.2	2.12
6000	47.7	22.9	2.08
0-20 MPH: 4.14
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.