

Boat Manufactured By:

CAROLINA SKIFF

3231 Fulford Road • Waycross, GA 31503

(912) 287-0547

www.carolinaskiff.com

CAROLINA SKIFF® 16 JVXCC

Length	15' 10"
Beam	6' 6"
Dry Weight (Boat Mfr. Pub)	973 lbs
Maximum HP	60 hp
Fuel Capacity	13 gal
Weight as Tested	1,720 lbs

F60LB

Horsepower	60 hp
Induction	EFI
Displacement	60.8 cu. in.
Weight (Estimated)	247 lbs
Gear Ratio	1.85

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

PROPELLER(S)

Series	Aluminum "G" Series
Diameter x Pitch	11 5/8 x 12
Yamaha Part #	69W-45952-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	58° F / 60° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes full tank of fuel, 1 battery, safety and test gear.

YPB#: PB_CSK_16JVXCC_F60LB_2013-11-14_SKF



Engine: Yamaha F60LB

F60LB

Boat: Carolina Skiff® 16 JVXCC

Configuration: Single

Test Date: 14-Nov-2013

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.2	0.3	10.67
1500	4	0.6	6.67
2000	5.2	0.9	5.78
2500	6.3	1.3	4.85
3000	9.1	1.9	4.79
3500	16.5	2	8.25
4000	22.1	2.3	9.61
4500	25.8	2.8	9.21
5000	29.5	3.4	8.68
5500	32	4.4	7.27
6050	34.5	5.8	5.95
Time to Plane : 3.61
 0-20 MPH: 5.49			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.