

Boat Manufactured By:



711 Boren Boulevard • Seminol, OK 74868

{0:(405) 382-0349}

www.bluewaveboats.com

BLUE WAVE® 2200 PURE BAY

Length	21' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	1,700 lbs
Maximum HP	250 hp
Fuel Capacity	60 gal
Weight as Tested	2,730 lbs

F200XB

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1 on 10" Hydraulic Jack Plate
------------------------	--------------------------------

PROPELLER(S)

Series	Pro Series™
Diameter x Pitch	14 1/2 x 21
Yamaha Part #	6J9-45976-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	45° F / 50° F
Elevation (in feet above sea level)	924'
Wind Velocity	15-20 MPH

COMMENTS

Test weight includes 15 gallons of fuel, 1 battery, 10" hydraulic jack plate, safety and test gear.

YPB#: PB_BWB_2200PureBay_F200XB_2013-04-18_BAY



Engine: Yamaha F200XB

F200XB

Boat: Blue Wave® 2200 Pure Bay

Configuration: Single

Test Date: 18-Apr-2013

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	0.8	5.88
1500	6.5	1.4	4.64
2000	7.8	2.7	2.89
2500	9.9	4.1	2.42
3000	26.4	4.5	5.87
3500	33.2	5.7	5.83
4000	38.6	7.8	4.95
4500	43.4	9.5	4.57
5000	48.8	13.1	3.73
5500	54.1	17.2	3.15
5900	56.4	18.6	3.03
Time to Plane : 4
 0-30 MPH: 7.45			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.