

Boat Manufactured By:



BENNINGTON
 2805 Decio Drive • Elkhart, IN 46514
 (0:(574) 264-6336)
 www.benningtonmarine.com

BENNINGTON® 21 SLX

Length	22' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,504 lbs
Maximum HP	150 hp
Fuel Capacity	0 gal
Pontoons Diameter	3 / SPS
Weight as Tested	3,504 lbs

F115XB

Horsepower	115 hp
Induction	EFI
Displacement	111.8 cu. in.
Weight (Estimated)	386 lbs
Gear Ratio	2.15

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Pontoon Performance Series
Diameter x Pitch	14 x 13
Yamaha Part #	MAR-PNTN3-V4-13
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	74° F / 76° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_BNT_21SLX_F115XB_2014-10-28_PNT



Engine: Yamaha F115XB

F115XB

Boat: Bennington® 21 SLX

Configuration: Single

Test Date: 28-Oct-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.1	0.5	8.2
1500	5.6	0.9	6.22
2000	7.2	1.4	5.14
2500	9	2	4.5
3000	13.8	2.5	5.52
3500	17.4	3.4	5.12
4000	21.1	4.4	4.8
4500	24.4	5.6	4.36
5000	27.9	6.9	4.04
5500	31.7	9.2	3.45
6000	35	10.8	3.24
0-20 MPH: 4.56
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.